Clawpack: building an open source ecosystem for solving hyperbolic PDEs

Kyle T. Mandli^{*} Aron J. Ahmadia[†] Marsha J. Berger[‡] Donna A. Calhoun[§]

David L. George[¶] Yiannis Hadjimichael[∥] David I. Ketcheson^{**}

Grady I. Lemoine^{††} Randall J. LeVeque^{‡‡}

May 13, 2016

Abstract

CLAWPACK is a software package designed to solve nonlinear hyperbolic partial differential equa-2 tions using high-resolution finite volume methods based on Riemann solvers and limiters. The pack-3 age includes a number of variants aimed at different applications and user communities. CLAWPACK 4 has been actively developed as an open source project for over 20 years. The latest major release, 5 CLAWPACK 5, introduces a number of new features and changes to the code base and a new devel-6 opment model based on GitHub and Git submodules. This article provides a summary of the most 7 significant changes, the rationale behind some of these changes, and a description of our current 8 development model. 9

10 1 Introduction

1

The CLAWPACK software suite [14] is designed for the solution of nonlinear conservation laws, balance 11 laws, and other first-order hyperbolic partial differential equations not necessarily in conservation form. 12 The underlying solvers are based on the wave propagation algorithms described by LeVeque in [39], and 13 are designed for logically Cartesian uniform or mapped grids or an adaptive hierarchy of such grids. 14 The original CLAWPACK was first released as a software package in 1994 and since then has made major 15 strides in both capability and interface. More recently a major refactoring of the code and a move 16 to GitHub for development has resulted in the release of CLAWPACK 5.0 in January, 2014. Beyond 17 enabling a distributed and better managed development process a number of user-facing improvements 18 were made including a new user interface and visualization tools, incorporation of high-order accurate 19 algorithms, parallelization through MPI and OpenMP, and other enhancements. 20

Because scientific software has become central to many advances made in science, engineering, resource management, natural hazards modeling and other fields, it is increasingly important to describe and document changes made to widely used packages. Such documentation efforts serve to orient new and existing users to the strategies taken by developers of the software, place the software package in

^{*}Columbia University (kyle.mandli@columbia.edu)

[†]Continuum Analytics (aahmadia@continuum.io)

[‡]New York University (berger@cims.nyu.edu)

[§]Boise State University (donnacalhoun@boisestate.edu)

[¶]USGS Cascades Volcano Observatory (dgeorge@usgs.gov)

^{||}King Abdullah University of Science and Technology, Box 4700, Thuwal, Saudi Arabia, 23955-6900 (yiannis.hadjimichael@kaust.edu.sa)

^{**}King Abdullah University of Science and Technology, Box 4700, Thuwal, Saudi Arabia, 23955-6900 (david.ketcheson@kaust.edu.sa)

^{††}CD-Adapco, Bellevue, WA

^{‡‡}Dept. of Applied Mathematics, University of Washington (rjl.@uw.edu)

²⁵ the context of other packages, document major code changes, and provide a concrete, citable reference

- ²⁶ for users of the software.
- 27 With this in mind, the goals of this paper are to:
- Summarize the development history of CLAWPACK,
- Summarize some of the major changes made between the early CLAWPACK 4.x versions and the most recent version, CLAWPACK 5.3,
- Summarize the development model we have adopted, for managing open source scientific software projects with many contributors, and
- Identify how users can contribute to the CLAWPACK suite of tools.

This paper provides a brief history of CLAWPACK in Section 1.1, a background of the mathematical concerns in Section 1.2, the modern development approach now being used in Section 2, the major feature additions in the CLAWPACK 5.x major release up until Version 5.3 in Section 3. Some concluding thoughts and future plans for CLAWPACK are mentioned in Section 4.

1.1 History of CLAWPACK

The first version of CLAWPACK was released by LeVeque in 1994 [37] and consisted of Fortran code 39 for solving problems on a single, uniform Cartesian grid in one or two space dimensions, together with 40 some MATLAB [45] scripts for plotting solutions. The wave-propagation method implemented in this 41 code provided a general way to apply recently developed high-resolution shock capturing methods to 42 general hyperbolic systems and required only that the user provide a "Riemann solver" to specify a 43 new hyperbolic problem. Collaboration with Berger [9] soon led to the incorporation of adaptive mesh 44 refinement (AMR) in two space dimensions, and work with Langseth [36, 35] led to three-dimensional 45 versions of the wave-propagation algorithm and the software, with three-dimensional AMR then added 46 by Berger. 47 Version 4.3 of CLAWPACK contained a number of other improvements to the code and formed the 48

⁴³ basis for the examples presented in a textbook [39] published in 2003. That text not only provided a ⁵⁰ complete description of the wave propagation algorithm, developed by LeVeque, but also is notable in ⁵¹ that the codes used to produce virtually all of figures in the text were made available online [39].

In 2009, CLAWPACK Version 4.4 was released with a major change from MATLAB to Python as the recommended visualization tool, and the development of a Python user interface for specifying the input data.

In 2009, CLAWPACK Version 4.4 was released with a major change from MATLAB to Python as the recommended visualization tool, and the development of a Python user interface for specifying the input data. Finally in January of 2013 the 4.x versions of CLAWPACK ended with the release of 4.6.3¹

Version 5 of CLAWPACK introduces both user-exposed features and a number of modern approaches to code development, interfacing with other codes, and adding new capabilities. The move to git version control also allowed a more complete open source model. These changes are the subject of the rest of this paper.

62 1.2 Hyperbolic problems

⁶³ In one space dimension, the hyperbolic systems solved with CLAWPACK typically take the form of ⁶⁴ conservation laws

65

$$q_t(x,t) + f(q(x,t))_x = 0$$
(1)

¹Details of these changes can be found at http://depts.washington.edu/clawpack/users-4.6/changes.html. Version 4.x used svn version control and the freely available software (under the BSD license) was distributed via tarballs.

66 or non-conservative linear systems

67

79

$$q_t(x,t) + A(x)q(x,t)_x = 0,$$
(2)

where subscripts denote partial derivatives and q(x,t) is a vector with $m \ge 1$ components. Here the 68 components of q represent conserved quantities, while the function f represents the flux (transport) 69 of q. Equation (1) generalizes in a natural way to higher space dimensions; see the examples below. 70 The coefficient matrix A in (2) or the Jacobian matrix f'(q) in (1) is assumed to be diagonalizable 71 with real eigenvalues for all relevant values of q, x, and t. This condition guarantees that the system 72 is hyperbolic, with solutions that are wave-like. The eigenvectors of the system determine the relation 73 between the different components of the system, or waves, and the eigenvalues determine the speeds at 74 which these waves travel. The right hand side of these equations could be replaced by a "source term" 75 $\psi(q, x, t)$ to give a non-homogeneous equation that is sometimes called a "balance law" rather than a 76 conservation law. Spatially-varying flux functions f(q, x) in (1) can also be handled using the f-wave 77 approach [5]. 78

Examples of equations solved by CLAWPACK include:

• Advection equation(s) for one or more tracers; in the simplest, one-dimensional case we have:

$$q_t + (u(x,t)q)_x = 0.$$

The velocity field u(x,t) is typically prescribed from the solution to another fluid flow problem, such as wind. Typical applications include transport of heat, energy, pollution, smoke, or another passively-advected quantity that does not influence the velocity field.

• The shallow water equations, describing the velocity (u, v) and surface height h of a fluid whose depth is small relative to typical wavelengths.

$$h_t + (hu)_x + (hv)_y = 0 (3)$$

$$(hu)_t + \left(hu^2 + \frac{1}{2}gh^2\right)_x + (huv)_y = -gb_x \tag{4}$$

$$(hv)_t + \left(hv^2 + \frac{1}{2}gh^2\right)_y + (huv)_x = -gb_y \tag{5}$$

Here g is a constant related to the gravitational force and b(x, y) is the *bathymetry*, or bottom surface height. Notice that the bathymetry enters the equations through a *source term*; additional terms could be added to model the effect of bottom friction. These equations are used, for instance, to model inundation caused by tsunamis and dam breaks, as well as to model atmospheric flows.

 The Euler equations of compressible, inviscid fluid dynamics, consist of conservation laws for mass, momentum, and energy. The wave speeds depend on the local fluid velocity and the acoustic wave velocity (sound speed). Source terms can be added to include the effect of gravity, viscosity or heat transfer. These systems have important applications in aerodynamics, climate and weather modeling, and astrophysics.

• Elastic wave equations, used to model compressional and shear waves in solid materials. Here even linear models can be complex due to varying material properties on multiple scales that affect the wave speeds and eigenvectors.

Discontinuities (shock waves) can arise in the solution of nonlinear hyperbolic equations, causing difficulties for traditional numerical methods based on discretizing derivatives directly. Modern shock capturing methods are often based on solutions to the *Riemann problem* that consists of equations (1) or (2) together with piecewise constant initial data with a single jump discontinuity. The solution to ⁹⁹ the Riemann problem is a similarity solution (a function of x/t only), typically consisting of m waves ¹⁰⁰ (for a system of m equations) propagating at constant speed. This is true even for nonlinear problems, ¹⁰¹ where the waves may be shocks or rarefaction waves (through which the solution varies continuously in ¹⁰² a self-similar manner).

The main theoretical and numerical difficulties of hyperbolic problems involve the prescription of physically correct weak solutions and understanding the behavior of the solution at discontinuities. The Riemann solver is an algorithm that encodes the specifics of the hyperbolic system to be solved, and it is the only routine (other than problem-specific setup such as initial conditions) that needs to be changed in order to apply the code to different hyperbolic systems. In some cases, the Riemann solver may also be designed to enforce physical properties like positivity (e.g., for the water depth in GEOCLAW) or to account for forces (like that of gravity) that may be balanced by flux terms.

CLAWPACK is based on Godunov-type finite volume methods in which the solution is represented 110 by cell averages. Riemann problems between the cell averages in neighboring states are used as the 111 fundamental building block of the algorithm. The wave-propagation algorithm originally implemented 112 in CLAWPACK (and still used in much of the code) is based on using the waves resulting from each 113 Riemann solution together with limiter functions to achieve second-order accuracy where the solution is 114 smooth together with sharp resolution of discontinuities without spurious numerical oscillations (see [39] 115 for a detailed description of the algorithms). Higher-order WENO methods have also been developed 116 relying on the same Riemann solvers. These methods can be found in PYCLAW (see Section 3.6), one 117 of the packages in the larger CLAWPACK ecosystem. 118

Problem-specific boundary conditions must also be imposed, which are implemented by a subroutine that sets the solution value in *ghost cells* exterior to the domain each time step. The CLAWPACK software contains library routines that implement several sets of boundary conditions that are commonly used, *e.g.* periodic boundary conditions, reflecting solid wall boundary conditions for problems such as acoustics, Euler, or shallow water equations, and non-reflecting (absorbing) extrapolation boundary conditions. As with all CLAWPACK library routines, the boundary condition routine can be copied and modified by the user to implement other boundary conditions needed for a particular application.

¹²⁶ In two or three space dimensions, the wave-propagation methods are extended using either dimen-¹²⁷ sional splitting, so that only one-dimensional Riemann solvers are needed, or by a multi-dimensional ¹²⁸ algorithm based on *transverse Riemann solvers* introduced in [38]. Both approaches are supported in ¹²⁹ CLAWPACK. A variety of Riemann solvers have been developed for CLAWPACK, many of which are ¹³⁰ collected in the riemann repository, see Section 3.2.

Adaptive mesh refinement (AMR) is essential for many problems and has been available in two 131 space dimensions since 1995, when Marsha Berger joined the project team and her AMR code for the 132 Euler equations of compressible flow was generalized to fit into the software which became AMRCLAW 133 [10], another package included in the CLAWPACK ecosystem. AMRCLAW was carried over to three 134 space dimensions using the unsplit algorithms introduced in [36]. Starting in Version 5.3.0, dimensional 135 splitting is also supported in AMRCLAW, which can be particularly useful in three space dimensions 136 where the unsplit algorithms are much more expensive. Other recent improvements to AMRCLAW are 137 discussed in Section 3.4. 138

There are several other open source software projects that provide adaptive mesh refinement for hyperbolic PDEs. The interested reader may want to investigate AMROC [16], BoxLib², Chombo [1], Gerris [50], OpenFOAM [46], or SAMRAI [3], for example.

¹⁴² 2 Development Approach

¹⁴³ CLAWPACK's development model is driven by the needs of its developer community. The CLAWPACK ¹⁴⁴ project consists of several interdependent projects: core solver functionality, a visualization suite, a ¹⁴⁵ general adaptive mesh refinement code, a specialized geophysical flow code, and a massively parallel ¹⁴⁶ Python framework. Changes to the core solvers and visualization suite have a downstream effect on the

²https://ccse.lbl.gov/BoxLib/index.html

other codes, and the developers largely work in an independent, asynchronous manner across continents
 and time zones.

- and time zones.
 The core CLAWPACK software repositories are:
- clawpack responsible for installation and coordination of other repositories,
- riemann Riemann solvers used by all the other projects,
- visclaw a visualization suite used by all the other projects,
- clawutil utility functions used by most other projects,
- classic the original single grid methods in 1, 2, and 3 space dimensions,
- amrclaw the general adaptive mesh refinement framework in 2 and 3 dimensions,
- geoclaw solvers for depth-averaged geophysical flows which employs the framework in amrclaw,
 and
- pyclaw a Python implementation and interface to the CLAWPACK algorithms including highorder methods and massively parallel capabilities.

A release of CLAWPACK downloaded by users contains all of the above. The repositories riemann, visclaw, and clawutil are sometimes referred to as *upstream* projects, since their changes affect all the remaining projects in the above list, commonly referred to as *downstream* projects. There are some variations on this, for instance AMRCLAW is upstream of GEOCLAW, which uses many of the algorithms and software base from AMRCLAW. To coordinate this the clawpack repository points to the most recent known-compatible version of each repository.

Beyond the major core code repositories, additional repositories contain documentation and extended examples for using the packages:

- doc the primary documentation source files. These files are written in the markup language reStructured Text³, and are then converted to html files using Sphinx⁴. Other documentation such as drafts of this paper are also found in this repository.
- clawpack.github.com the html files created by Sphinx in the doc repository are pushed to this repository, and are then automatically served on the web. These appear at http://www.
 clawpack.org, which is configured to point to http://clawpack.github.com. The name of this repository follows GitHub convention for use with GitHub Pages⁵.
- apps applications contributed by developers and users that go beyond the introductory examples
 included in the core repositories.

¹⁷⁷ The CLAWPACK 4.x code is also available in the repository clawpack-4.x but is no longer under ¹⁷⁸ development.

¹⁷⁹ 2.1 Version Control

The CLAWPACK team uses the Git distributed version control system to coordinate development of each major project. The repositories are publicly coordinated under the CLAWPACK organization on GitHub⁶ with the top-level clawpack super-repository responsible for hosting build and installation tools, as well as providing a synchronization point for the other repositories. The remaining "core CLAWPACK repositories" listed above are subrepositories of the main clawpack organization.

³http://www.sphinx-doc.org/en/stable/rest.html

⁴http://sphinx-doc.org

⁵https://pages.github.com/ ⁶https://github.com/clawpack

GitHub itself is a free provider of public Git repositories. In addition to repository hosting, the 185 CLAWPACK team uses GitHub for issue tracking, code review, automated continuous integration via 186 Travis CI⁷, and test coverage tracking via Coveralls⁸ for the Python-based modules. The issue tracker on 187 GitHub supports cross-repository references, simplifying communication between CLAWPACK developer 188 sub-teams. The Travis CI service, which provides free continuous integration for publicly developed 189 repositories on GitHub, runs CLAWPACK's test suites through nose⁹ on proposed changes to the code 190 base, and through a connection to the Coveralls service, reports on any test failures as well as changes 191 to test coverage. 192

¹⁹³ 2.2 Submodules

The clawpack "super-repository" serves two purposes. First, it contains installation utilities for each of the sub-projects. Second, it serves as a synchronization point for the project repositories. The remainder of this section provides more details on how Git submodules enable this synchronization.

Whenever possible, teams of software developers coordinate their development in a single unified repository. In situations where this isn't possible, one option provided by Git is the submodule, which allows a super-repository (in this case, clawpack), to nest sub-repositories as directories, with the ability to capture changes to sub-repository revisions as new revisions in the super-repository. Under the hood, the super-repository maintains pointers to the location of each submodule and its current revision. The submodule directories contain normal Git repositories, all of the coordination happens in the super-repository.

Each of the other core CLAWPACK repositories listed above is a submodule of the clawpack repository. Every commit that creates a new revision to the clawpack repository describes top-level installation code as well as the revisions of each of the submodules. In this way, Git submodules allow CLAWPACK team members to work asynchronously on independent projects while reusing and maintaining common software infrastructure.

Typically the CLAWPACK developers advance the master development branch of the top-level clawpack repository any time a major feature is added or a bug is fixed in one of the upstream projects that might affect code in other repositories. By checking out a particular revision in the clawpack repository and performing a git submodule update, all repositories can be updated to versions that are intended to be consistent and functional.

In particular, when Travis CI runs the regression tests in any project repository (performed automatically for any pull request), it starts by installing CLAWPACK on a virtual machine and the current head of the clawpack/master branch indicates the commit from each of the other projects that must be checked out before performing the tests. If the clawpack repository has not been properly updated following changes in other upstream projects, these tests may fail.

Any new release of CLAWPACK is a snapshot of one particular revision of clawpack and the related revisions of all submodules. These particular revisions are also tagged for future reference with consistent names, such as v5.3.1. (Git tags simply provide a descriptive name for a particular revision rather than having to refer to a Git hash code.)

223 2.3 Contributing

Scientists who program are often discouraged from sharing code due to existing reward mechanisms and the fear of being "scooped". However, recent studies indicate that scientific communities that openly share and develop code have an advantage because each researcher can leverage the work of many others [53], and that paper citation rates can be increased by sharing code [54] and/or data [49]. Moreover, journals and funding agencies are increasingly requiring investigators to share code used to obtain published results. One of the goals of the CLAWPACK project is to facilitate code sharing by

⁷https://travis-ci.org/ ⁸http://coveralls.io ⁹https://nose.readthedocs.org

users, by providing an easy mechanism to refer to a specific version of the CLAWPACK software and
 ensuring that past versions of the software remain available on a stable and citable platform.

On the development side, we expect that the open source development model with important dis-232 cussions conducted in public will lead to further growth of the developer community and additional 233 contributions from users. Over the past twenty years, many users have written code extending CLAW-234 PACK with new Riemann solvers, algorithms, or domain-specific problem tools. Unfortunately, much 235 of this code did not make it back into the core software for others to use. Many of the development 236 changes in CLAWPACK 5.x were done to encourage contributions from a broader community. We have 237 begun to see an increase in contributions from outside the developers' groups, and hope to encourage 238 more of this in the future. 239

The primary development model is typical for GitHub projects: a contributor forks the repository 240 on GitHub, then develops improvements in a branch that is pushed to her own fork. She issues a "pull 241 request" (PR) when the branch is ready to be merged into the main repository. Increasingly, contributors 242 are also using PRs as a way to conveniently post preliminary or prototype code for discussion prior to 243 further development, often marked WIP for "work in progress" to signal that it is not ready to merge. 244 After a PR is issued, other developers, including one or more of the maintainers for the corresponding 245 project, review the code. The Travis CI server also automatically runs the tests on the proposed new 246 code. The test results are visible on the GitHub page for the PR. Usually there is some iteration as 247 developers suggest improvements or discuss implementation choices in the code. Once the tests are 248 passing and it is agreed that the code is acceptable, a maintainer merges it. 249

An additional benefit of using the GitHub platform is that any version of the code is accessible either through the command line git interface, through the GitHub website, or a number of available applications on all widely used platforms. More important however is the ability to tag a particular version of a repository with a digital object identifier (DOI) via GitHub and Zonodo¹⁰. The combination of these abilities provides the capability for CLAWPACK to not only be accessible at any version but also allows for the citability of versions of the code used for particular results within the scientific literature.

256 2.4 Releases

Although CLAWPACK is continuously developed, it is convenient for users to be able to install stable
versions of the software. The CLAWPACK developers provide these releases through two distribution
channels: GitHub and the Python Package Index (PyPI). Full source releases are available on GitHub.
Alternatively, the PYCLAW subproject and its dependencies can be installed automatically using a PyPI
client such as pip.

CLAWPACK does not follow a calendar release cycle. Instead, releases emerge when the developer 262 community feels enough changes have accumulated since the last release to justify the cost of switching to 263 a new release. For the most part, CLAWPACK releases are versioned using an M.m.p triplet, representing 264 the major (M), minor (m), and patch (p) versions respectively. In the broader software engineering 265 community, this is often referred to as semantic versioning. Small changes that fix bugs and cosmetic 266 issues result in increments to the patch-level. Backwards-compatible changes result in an increase to the 267 minor version. The introduction of backwards-incompatible changes require that the major version be 268 incremented. In addition, the implementation of significant new algorithms or capability will also justify 269 the increment of major release number, and is often an impetus for providing another release to the 270 public. In practice, the CLAWPACK software has frequently included changes in minor version releases 271 that were not entirely backwards compatible, but these have been relatively minor and documented in 272 the release notes. Major version numbers have changed infrequently and related to major refactoring 273 of the code as in going from 4.x to 5.0. 274

Staring with Version 5.3.1, the tarfiles for Clawpack releases will also be archived on Zenodo¹¹, a data repository hosted at CERN that issues DOIs so that the software version can be cited with a

 $^{^{10}{\}rm For}$ a guide on creating a DOI to a particular version of software see http://guides.github.com/activities/citable-code/

¹¹https://zenodo.org

²⁷⁷ permanent link [52] that does not depend on the long-term existence of GitHub.

278 2.5 Dependencies

Running any part of CLAWPACK requires a Python interpreter and the common Python packages numpy
[30], f2py [48], matplotlib [27], as well as (except for the pure-Python 1D code) GNU make and a Fortran
compiler. Other dependencies are optional, depending on which parts of CLAWPACK are to be used:

- IPython/Jupyter if using the notebook interfaces [47].
- PETSc [4], if using distributed parallelism in PYCLAW.

• OpenMP, if using shared-memory parallelism in AMRCLAW or GEOCLAW.

• MATLAB, if using the legacy visualization tools.

286 **3** Advances

This section describes the major changes in each of the code repositories in moving from CLAWPACK 4.x to the most recent version 5.3. A number of the repositories have seen only minor changes as the bulk of the development is focused on current research interests. There are a number of minor changes not listed here and the interested reader is encouraged to refer to the change logs¹² and the individual CLAWPACK Git repositories for a more complete list.

²⁹² 3.1 Global Changes

Substantial redesign of the CLAWPACK code base was performed in the move from CLAWPACK 4.x to
 5.x. Major changes that affected all aspects of the code include:

• The interface to the CLAWPACK Riemann solvers was changed so that one set of solvers can be used for all versions of the code (including PYCLAW via f2py¹³). Rather than appearing in scattered example directories, these Riemann solvers have all been collected into the new riemann repository. Modifications to the calling sequences were made to accommodate this increased generality.

• Calling sequences for a number of other Fortran subroutines were also modified based on experiences with the CLAWPACK 4.x code. These can also be used as a stand-alone product for those who only want the Riemann solvers.

Python front-ends were redesigned to more easily specify run-time options for the solver and visualization. The Fortran variants (CLASSICCLAW, AMRCLAW, and GEOCLAW) all use a Python script to facilitate setting input variables. These scripts create text files with a rigidly specified format that are then read in when the Fortran code is run. The interface now allows updates to the input parameters while maintaining backwards compatibility.

• The indices of the primary conserved quantities were reordered. In CLAWPACK 4.x, the *m*th component of a system of equations in grid cell (i, j) (in two dimensions, for example), was stored in q(i,j,m). In order to improve cache usage and to more easily interface with PETSc [4], a global change was made to the ordering so that the component number comes first; i.e. q(m,i,j). A seemingly minor change like this affects a huge number of lines in the code and cannot easily be automated. The use of version control and regression tests was crucial in the successful completion of the project.

¹²http://www.clawpack.org/changes.html

¹³http://docs.scipy.org/doc/numpy-dev/f2py

315 3.2 Riemann: A Community-Driven Collection of Approximate Riemann 316 Solvers

The methods implemented in CLAWPACK, and all modern Godunov-type methods for hyperbolic PDEs, are based on the solution of Riemann problems as discussed in Section 1.2. Whereas most existing codes for hyperbolic PDEs use Riemann solvers to compute fluxes, CLAWPACK Riemann solvers instead compute the waves (or discontinuities) that make up the Riemann solution. In the unsplit algorithm, CLAWPACK also makes use of *transverse* Riemann solvers, responsible for computing transport between cells that are only corner (in 2d) or edge (in 3d) adjacent.

For nonlinear systems, the exact solution of the Riemann problem is computationally costly and may involve both discontinuities (shocks and contact waves) and rarefactions. It is almost always preferable to employ inexact Riemann solvers that approximate the solution using discontinuities only, with an appropriate entropy condition. The solvers available in CLAWPACK are all approximate solvers, although one could easily implement their own exact solver and make it available in the format needed by CLAWPACK routines.

A common feature in all packages in the CLAWPACK suite is the use of a standard interface for Fortran Riemann solver routines. This ensures that new solvers or solver improvements developed for one package can immediately be used by all packages. To further facilitate this sharing and to avoid duplication, Riemann solvers are (with rare exceptions) not maintained under the other packages but are collected in a single repository named **riemann**. Users who develop new solvers for CLAWPACK are encouraged to submit them to the Riemann repository.

In the Fortran-based packages (Classic, AMRClaw, and GeoClaw) the Riemann solver is selected at compile-time by modifying a problem-specific Makefile. In PYCLAW, the Riemann solver to be used is selected at run-time. This is made possible by compiling all of the Riemann solvers (when PYCLAW is installed) and generating Python wrappers with f2py. For PYCLAW, riemann also provides metadata (such as the number of equations, the number of waves, and the names of the conserved quantities) for each solver so that setup is made more transparent.

341 3.3 CLASSICCLAW

The classic repository contains code implementing the wave propagation algorithm on a single uniform grid, in much the same form as the original CLAWPACK 1.0 version of 1994 but with various enhancements added through the years. Following the introduction of CLAWPACK 4.4 the three-dimensional routines were left out of the Python user interfaces and plotting routines. These have been reintroduced in CLAWPACK 5. Additionally the OpenMP shared-memory parallelism capabilities have been extended to the three-dimensional code.

348 **3.4** AMRCLAW

Fortran code in the AMRCLAW repository performs block-structured adaptive mesh refinement [6, 7] for both CLAWPACK and GEOCLAW applications. The algorithms implemented in AMRCLAW are discussed in detail in [9, 41], but a short description is given here to set the stage for a description of recent changes. This type of refinement solves the PDE on a hierarchy of logically rectangular grids. One (or more) level 1 grids comprise the entire domain, while grids at finer level are created and destroyed (as opposed to moving these grids) to follow important features in the solution.

355 AMRCLAW includes the functionality for:

• Coordinating the flagging of points where refinement is needed, with a variety of criteria possible for flagging cells that need refinement from each level to the next finer level (including Richardson extrapolation, gradient testing, or user-specified criteria)¹⁴,

¹⁴See http://www.clawpack.org/flag.html



Figure 1: An illustration showing grid cells on levels one and two, and only grid outlines on levels three and four.

- Organizing the flagged points into efficient grid patches at the next finer level, using the algorithm of [11],
- Interpolating the solution to newly created fine grids and initializing auxiliary data (topography, wind velocity, metric data and so on) on these grids,
- Averaging fine grid solutions to coarser grids,
- Orchestrating the adaptive time stepping (i.e. sub-cycling in time),
- Interpolating coarse grid solution to fine grid ghost cells, and
- Maintaining conservation at patch boundaries between resolution levels.

AMRCLAW now allows users to specify "regions" in space-time $[x_1, x_2] \times [y_1, y_2] \times [t_1, t_2]$ in which refinement is forced to be at least at some level L_1 and is allowed to be at most L_2 . This can be useful for constraining refinement, e.g. allowing or ensuring resolution of only a small coastal region in a global tsunami simulation. Previously the user could enforce such conditions by writing a custom flagging routine, but now this is handled in a general manner so that the parameters above can all be specified in the Python problem specification. Multiple regions can be specified, and a simple rule is used to determine the constraints at a grid cell that lies in multiple regions.

Auxiliary arrays are often used in CLAWPACK to store data that describes the problem and the routine. The routine **setaux** must then be provided by the user to set these values each time a new grid patch is created. For some applications computing these values can be time-consuming. In CLAWPACK 5.2, this code was improved to allow reuse of values from previous patches at the same level where possible at each regridding time. This is backward compatible, since no harm is done if previously written routines are used that still compute and overwrite instead of checking a mask.

In CLAWPACK 5.3 the capability to specify spatially varying boundary conditions was added. For a single grid, it is a simple matter to compute the location of the ghost cells that extend outside the computational domain and set them appropriately. With AMR however, the boundary condition routine can be called for a grid located anywhere in the domain, and may contain fewer or larger numbers of ghost cells. For this reason, the boundary condition routines do not assume a fixed number of ghost cells.

Anisotropic refinement is allowed in both two and three dimensions. This means that the spatial and temporal refinement ratios can be specified independently from one another (as long as the temporal refinement satisfies the CFL condition). In addition, capabilities have been added to automatically select the refinement ratio in time on each level based on the CFL condition. This has only been



Figure 2: AMRCLAW example demonstrating a shock-bubble interaction in the Euler equations of compressible gas-dynamics at two times, illustrating the need for adaptive refinement to capture localized behavior. There are two $20 \times 10 \times 10$ grids at level 1. They are refined where needed by factors of 4 and then 2 in this 3-level run.

implemented in GEOCLAW where the wave speed in the shallow water equations depends on the local
 depth. The finest grids are often located only in shallow coastal regions, so a large refinement ratio in
 space does not lead to a large refinement ratio in time.

AMRCLAW has been parallelized using OpenMP directives. The main paradigm in structured AMR 393 is an outer loop over levels of refinement, and in inner loop overall grids at that level, where the same 394 operation is performed on each grid (i.e. taking a time step, finding ghost cells, conservation updates, 395 etc.). This inner loop is parallelized using a parallel for loop construct one thread is assigned to 396 operate on one grid. Dynamic scheduling is used with a chunk size of one. To help with load balancing, 397 grids at each level are sorted from largest to smallest, using the total number of cells in the grid as an 398 indicator of work. In addition there is a grids are limited to a maximum of 32 cells in each dimension, 399 otherwise they are bisected until this condition is met. Note that this approach causes a memory bulge. 400 Each thread must have its own scratch arrays to save the incoming and outgoing waves and fluxes for 401 future conservation fix-ups. The bulge is directly proportional to the number of threads executing. 402 For stack-based memory allocation per thread, the use of the environment variable OMP_STACKSIZE to 403 increase the limit may be necessary. 404

Fig. 2 shows two snapshots of the solution to a three-dimensional shock-bubble interaction problem 405 found in the CLAWPACK apps repository, illustrating localized phenomena requiring adaptive refine-406 ment. In Fig. 3 we show scalability tests and some timings for this example, when run on a 40 core 407 Intel Xeon Haswell machine (E5-2670v3 at 2.3 GHz), using KMP_AFFINITY compact with one thread 408 per core. For timing purposes, the only modifications made to the input parameters was to turn off 409 check-pointing and graphics output. The plot on the left shows that most of the wall clock time is in the 410 integration routine (stepgrid), which closely tracks the total time. The second chunk of time is in the 411 regridding, which contains algorithms that are not completely scalable. Very little time is in the filling 412 of ghost cells, mostly from other patches but also includes those at domain boundaries. The efficiency 413 is above 80% until 24 cores, then drops off dramatically. Note that there are only two grids on level, 414 and an average of 22.8 level 2 grids. Most of the work is on level 3 grids, where there are an average 415 of 138.1 grids over all the level 3 timestep. This is very coarse for large numbers of cores (hence the 416 dropoff in efficiency). At 40 cores, there are less than 4 grids per core, and the grids are very different 417 sizes. 418

⁴¹⁹ The target architecture for AMRCLAW and GEOCLAW are multi-core machines. PYCLAW on the ⁴²⁰ other hand scales to tens of thousands of cores using MPI via PETSc [4] but is not adaptive.



Figure 3: Left is strong scaling results for the AMRCLAW example shown in Fig. 2. Right is plot of efficiency based on total computational time.

421 **3.5** GeoClaw

The GEOCLAW branch of CLAWPACK was developed to solve the two-dimensional shallow water equations over topography for modeling tsunami generation, propagation, and inundation. The AMRCLAW code formed the starting point but it was necessary to make many modifications to support the requirements of this application, as described briefly below. This code originated with the work of George [19, 20, 21] and was initially called TSUNAMICLAW. Later it became clear that many other geophysical flow applications have similar requirements and the code was generalized as GEOCLAW.

One of the major issues is the treatment of wetting and drying of grid cells at the margins of the 428 flow. The handling of dry states in a Riemann solver is difficult to handle robustly, and has gone 429 through several iterations. GEOCLAW must also be well-balanced in order to preserve steady states, in 430 particular the "ocean at rest". To achieve this, the source terms in the momentum equations arising 431 from variations in topography are incorporated into the Riemann solver rather than using a fractional 432 step splitting approach. This is critical for modeling waves that have very small amplitudes relative to 433 the variations in the depth of the ocean. See [40] for a general discussion of such methods and [20, 21]434 for details of the Riemann solver used in GEOCLAW. Other features of GEOCLAW include the ability to 435 solve the equations in latitude-longitude coordinates on the surface of the sphere, and the incorporation 436 of source terms modeling bottom friction using a Manning formulation. More details about the code 437 and tsunami modeling applications can be found in [8, 41]. In 2011, a significant effort took place to 438 verify and validate GEOCLAW against the US National Tsunami Hazard Mitigation Program (NTHMP) 439 benchmarks [25]. NTHMP approval of the code allows GEOCLAW to be used in hazard mapping projects 440 that are funded by this program or other federal and state agencies, e.g. [23, 24]. One such project is 441 illustrated in Fig. 4. 442

In addition to a variety of tsunami modeling applications, GEOCLAW has been used to solve dam break problems in steep terrain [18], storm surge problems [44] (see Fig. 5), and submarine landslides [34]. The code also formed the basis for solving the multi-layer shallow water equations for storm surge modeling [42, 43], and is currently being extended further to handle debris flow modeling in the packages D-Claw [28, 22] (see Figs. 6 and 7).

⁴⁴⁸ Nearly one quarter of the files in the AMRCLAW source library have to be modified for GEOCLAW. ⁴⁴⁹ There are currently 113 files in the AMRCLAW 2D library, of which 26 are replaced by a GEOCLAW-⁴⁵⁰ specific files of the same name in the GEOCLAW 2D library. For example, to preserve a flat sea surface ⁴⁵¹ when interpolating, it is necessary to interpolate the surface elevation (topography plus water depth) ⁴⁵² rather than simply interpolating the depth component of the solution vector as would normally be done ⁴⁵³ in AMRCLAW. An additional 24 files in the GEOCLAW shallow water equations library handle other 454 complications introduced by the need to model tsunamis and storm surge.

455 Several other substantial improvements in the algorithms implemented in GEOCLAW have been 456 made between versions 4.6 and 5.3.0, including:

In depth-averaged flow, the wave speed and therefore the CFL condition depends on the depth.
 As a result, flows in shallow water that have been refined spatially may not need to be refined in time. This "variable-time-stepping" was easily added along with the anisotropic capabilities that were added to AMRCLAW.

• The ability to specify topography via a set of topo files that may cover overlapping regions at different resolutions has been added. The finite volume method requires cell averages of topography, computed by integrating a piecewise bilinear function constructed from the input topo files over each grid cell. In CLAWPACK 5.1.0, this was improved to allow an arbitrary number of nested topo grids. When adaptive mesh refinement is used, regridding may take place every few time steps. Improvements were made in 5.2.0 so that topography could be copied rather than always being recomputed in regions where there is an existing old grid.

• The user can now provide multiple dtopo files that specify changes to the initial topography at a series of times. This is used to specify sea-floor motion during a tsunamigenic earthquake, but can also be used to specify submarine landslide motion or a failing dam, for example.

• A number of new Python modules has been developed to assist the user in working with topo and dtopo files. These are documented in the CLAWPACK documentation and several of them are illustrated with Jupyter notebooks found in the CLAWPACK Gallery.

• New capabilities were added in 5.0.0 to monitor the maximum of various flow quantities over 474 a specified time range of a simulation. This capability is crucial for many applications where 475 the maximum flow depth at each point, maximum current velocities in a harbor, or maximum 476 momentum flux (a measure of the hydrodynamic force that would be exerted by the flow on a 477 structure) is desired. Arrival time of the first wave at each point can also be monitored. Such 478 capabilities were included in the 4.x version of the code, but were more limited and did not always 479 perform properly near the edges of refinement patches. In Version 5.2 these routines were further 480 improved and extended. The user can specify a grid of points on which to monitor values, and 481 the new code is more flexible in allowing one-dimensional grids (e.g. a transect), two-dimensional 482 rectangular grids, or an arbitrary set of points¹⁵. 483

484 **3.6** PyClaw

PYCLAW is an object-oriented Python package that provides a convenient way to set up problems and call the algorithms of CLAWPACK. It grew from what was initially a set of data structures and file IO routines that are used by the other CLAWPACK codes and by VISCLAW. These routines were released in an early form in later 4.x versions of CLAWPACK. Those releases also included a fullyfunctional implementation of the 1D classic algorithm in pure Python. That implementation still exists in PYCLAW and is useful for understanding the algorithm.

The current release of PYCLAW includes access to the classic algorithms as well as the high-order 491 algorithms introduced in SHARPCLAW [32] (i.e., WENO reconstruction and Runge–Kutta integrators) 492 and can be used on large distributed-memory parallel machines. For the latter capability, PYCLAW 493 relies on PETSc [4]. Lower-level code (whatever gets executed repeatedly and needs to be fast) from 494 the earlier Fortran Classic and SHARPCLAW codes is automatically wrapped at install time using f2py. 495 Recent applications of PYCLAW include studies of laser light trapping by moving refractive index 496 perturbations [51], instabilities of weakly nonlinear detonation waves [17], and effective dispersion of 497 nonlinear waves via diffraction in periodic materials [33]. Two of these are depicted in Fig. 8. 498

¹⁵Described in http://www.clawpack.org/fgmax.html



Figure 4: Gray's Harbor showing Westport, WA on southern peninsula. (Google map data and image, 2016.) (b) Simulation of a potential magnitude 9 Cascadia Subduction Zone event, 40 minutes after the earthquake. (c) Design for new Ocosta Elementary School in Westport, based in part on GEOCLAW simulations [23]. Image courtesy of TCF Architecture.



Figure 5: Top Left: A snapshot of a GEOCLAW storm surge simulation of Hurricane Ike at landfall. Top Right: Tide gauge data computed from GEOCLAW and ADCIRC along with observed data at the same location. Bottom: Computational effort and timings for GEOCLAW and ADCIRC. From [44].

⁴⁹⁹ **3.6.1** Librarization and extensibility

Scientific software is easier to use, extend, and integrate with other tools when it is designed as a 500 library [12]. CLAWPACK has always been designed to be extensible, but PYCLAW takes this further in 501 several ways. First, it is distributed via a widely-used package management system, pip. Second, the 502 default installation process ("pip install clawpack") provides the user with a fully-compiled code 503 and does not require setting environment variables. Like other CLAWPACK packages, PYCLAW provides 504 several "hooks" for users to plug in custom routines (for instance, to specify boundary conditions). In 505 PYCLAW, these routines - including the Riemann solver itself - are selected at run-time, rather than at 506 compile-time. These routines can be written directly in Python, or (if they are performance-critical) in a 507 compiled language (like Fortran or C) and wrapped with one of the many available tools. Problem setup 508 (including things like initial conditions, algorithm selection, and output specification) is also performed 509 at run-time, which means that researchers can bypass much of the slower code-compile-execute-post-510 process cycle. It is intended that PYCLAW be easily usable within other packages (without control of 511 main()). 512

513 3.6.2 Python geometry

PYCLAW includes Python classes for describing collections of structured grids and data on them. These
 classes are also used by the other codes and VISCLAW, for post-processing. A mesh in CLAWPACK always
 consists of a set of (possibly mapped) tensor-product grids (interval, quadrilateral, or hexahedral), also
 referred to as patches. At present, PYCLAW solvers operate only on a single patch, but the geometry
 and grids already incorporate multi-patch capabilities for visualization in AMRCLAW and GEOCLAW.

519 3.6.3 PYCLAW solvers

⁵²⁰ PyClaw includes an interface to both the Classic solvers (already described above) and those of SHARP-⁵²¹ CLAW [31]. SHARPCLAW uses a traditional method-of-lines approach to achieve high-order resolution in



Figure 6: (a) Photograph of the 2010 Mt. Meager debris-flow deposit, from [2]. (b) Simulated debris flow, from D. George.



Figure 7: Observed (yellow line) and computed (blue) landslide at Oso, WA in 2014 [29].

⁵²² space and time. Spatial operators are discretized first, resulting in a system of ODEs that is then solved ⁵²³ using Runge–Kutta or linear multistep methods. The spatial derivatives are computed using a weighted ⁵²⁴ essentially non-oscillatory (WENO) reconstruction from cell averages, which suppresses spurious oscilla-⁵²⁵ tions near discontinuities. The WENO routines in SHARPCLAW were generated by PyWENO¹⁶, which ⁵²⁶ is a standalone package that generates WENO routines.

The default time stepping routines in SHARPCLAW are strong stability preserving (SSP) Runge– Kutta methods of order two to four. Some of the methods use extra stages in order to allow more efficient time stepping with larger CFL numbers. Time stepping in SHARPCLAW has recently been augmented to include linear multistep methods with variable step size. These methods use a time step size selection that ensures the strong stability preserving property, as described in [26].

532 3.6.4 Parallelism

⁵³³ PYCLAW includes a distributed parallel backend that uses PETSc through the Python wrapper petsc4py. ⁵³⁴ The parallel code uses the same low-level routines without modification. In the high-level routines, only ⁵³⁵ a few hundred lines of Python code deal explicitly with parallel communication, in order to transfer ⁵³⁶ ghost cell information between subdomains and to find the global maximum CFL number in order to ⁵³⁷ adapt the time step size. For instance, the computation shown in the right part of Fig. 8 involved more

¹⁶http://github.com/memmett/PyWENO



Figure 8: Left: A two-dimensional detonation wave solution of the reactive Euler equations, showing transverse shocks that arise from instabilities; see [17]. Right: Dispersion of waves in a layered medium with matched impedance and periodically-varying sound speed; see [33].

 $_{538}$ than 120 million degrees of freedom and was run on two racks of the Shaheen I BlueGene/P supercom-

⁵³⁹ puter. The code has been demonstrated to scale with better than 90% efficiency in even larger tests on

tens of thousands of processors on both the Shaheen I (BlueGene/P) and Shaheen II (Cray XC40) su-

⁵⁴¹ percomputers at KAUST. A hybrid MPI/OpenMP version is already available in a development branch

⁵⁴² and will be included in future releases.

543 3.7 VisClaw : Visualizing CLAWPACK output

A practical way to visualize the results of simulations is essential to any software package for solving PDEs. This is particularly true for simulations making use of adaptive mesh refinement, since most available visualization packages do not have tools that conveniently visualize hierarchical AMR data. VISCLAW provides support for all of the main CLAWPACK submodules, including CLASSICCLAW, AMRCLAW, PYCLAW and GEOCLAW.

From the first release in 1994, CLAWPACK has included tools for visualizing the output of CLAWPACK 549 and AMRCLAW runs. Up until the release of version CLAWPACK 4.x, these visualization tools consisted 550 primarily of MATLAB routines for creating one, two and three dimensional plots including pseudo-color 551 plots, Schlieren plots, contour plots and scatter plots, including radially or spherically symmetric data. 552 Built-in tools were also available for handling one, two and three-dimensional mapped grids. Starting 553 with version 4.x, however, it was recognized that a reliance on proprietary software for visualization 554 prevented a sizable potential user base from making use of the CLAWPACK software. The one and two 555 dimensional plotting routines were converted from MATLAB to matplotlib, a popular open source Python 556 package for producing publication quality graphics for one and two dimensional data [27]. 557

With the development of CLAWPACK Version 5 and above, Python graphics tools have been collected 558 into the VISCLAW repository. The VISCLAW tools extend the functionality of the Version 4.x Python 559 routines for creating one and two dimensional plots, and adds several new capabilities. Chief among 560 these are the ability to generate output to webpages, where a series of plots can be viewed individually or 561 as an animated time sequence using the Javascript package¹⁷ (which was motivated by code in an earlier 562 version of CLAWPACK). The VISCLAW module Iplotclaw provides interactive plotting capabilities from 563 the Python or IPython prompt. Providing much of the same interactive capabilities as the original 564 MATLAB routines, Iplotclaw allows the user to step, interactively, through a time sequence of plots, 565 jump from one frame to another, or interactively explore data from the current time frame. 566

¹⁷https://github.com/jakevdp/JSAnimation

567 3.7.1 Tools for visualizing geo-spatial data produced by GEOCLAW

The geo-spatial data generated by GEOCLAW has particular visualization requirements. Tsunami or 568 storm surge simulations are most useful when the plots showing inundation or flooding levels are overlaid 569 onto background bathymetry or topography. Supplementary one dimensional time series data (e.g. 570 gauge data) numerically interpolated from the simulation at fixed spatial locations are most useful when 571 compared graphically to observational data. Finally, to more thoroughly analyze the computational 572 data, simulation data should be made available in formats that can be easily exported to GIS tools 573 such as ARCGIS¹⁸ or the open source alternative QGIS¹⁹. For exploration of preliminary results or 574 communicating results to non-experts, Google Earth is also helpful. 575

The latest release of CLAWPACK includes many specialized VISCLAW routines for handling the above issues with plotting geo-spatial data. Topography or bathymetry data that was used in the simulation will be read by the graphing routines, and, using distinct colormaps, both water and land can be viewed on the same plot. Additionally, gauge locations can be added, along with contours of water and land. One dimensional gauge plots are also created, according to user-customizable routines. In these gauge plotting routines, users can easily include observational data to compare with GEOCLAW simulation results.

In addition to HTML and Latex formats available for all CLAWPACK results, VISCLAW will now also 583 produce KML and KMZ files suitable for visualizing results in Google Earth. Using the same matplotlib 584 graphics routines, VISCLAW creates PNG files that can be used as GroundOverlav features in a KML 585 file. Other features, such as gauges, borders on AMR grids, and user specified regions can also be shown 586 on Google Earth. All KML and PNG files are compressed into a single KMZ file that can be opened 587 directly in Google Earth or made available on-line. While VISCLAW does not have any direct support 588 for ARCGIS or QGIS, the KML files created for Google Earth can be edited for export, along with 589 associated PNG files to these other GIS applications. 590

⁵⁹¹ 3.7.2 Matlab plotting routines

The MATLAB plotting tools available in early versions of CLAWPACK are still included in VISCLAW. While most of the one and two dimensional capabilities available originally in the MATLAB suite have been ported to Python and matplotlib, the original MATLAB routines are still available in the MATLAB suite of plotting tools. Other plotting capabilities, such as two dimensional manifolds embedded in three dimensional space, or three dimensional plots of fully three-dimensional data are only available in the MATLAB routines in a way that interfaces directly with CLAWPACK. More advanced three-dimensional plotting capabilities are planned for future releases of VISCLAW.

599 4 Conclusions

CLAWPACK has evolved over the past 20 years from its genesis as a small and focused software package 600 that two core developers could manage without version control. It is now an ecosystem of related projects 601 that share a core philosophy and some common code (notably Riemann solvers and visualization tools), 602 but that are aimed at different user communities and that are developed by overlapping but somewhat 603 distinct groups of developers scattered at many institutions. The adoption of better software engineering 604 practices, in particular the use of Git and GitHub as an open development platform and the use of pull 605 requests to discuss proposed changes, has been instrumental in facilitating the development of many of 606 the new capabilities summarized in this paper. These developer facing improvements of course affect 607 the user as well since better and faster development cycles means better and faster implementation 608 of features. The user facing features already implemented in version 5 have opened up the use of 609 CLAWPACK to a broader audience. 610

¹⁸http://www.arcgis.com ¹⁹http://www.qgis.org

611 4.1 Future Plans

The CLAWPACK development team continues to look forward to new ideas and efforts that will allow great accessibility to the project as well as new capabilities that the core development team has not thought of. To this end a number of the broad efforts that are being considered for the next major release of CLAWPACK include

- An increased librarization effort with the Fortran based sub-packages,
- An extensible and more accessible interface to the Riemann solvers,
- An effort to allow PYCLAW and the CLAWPACK Fortran packages to rely on more of the same code-base,
- An increased emphasis on a larger development community,
- More support for new frameworks such as FORESTCLAW [13],
- Adjoint error estimation for flagging cells to increase the efficiency of the AMR codes [15],
- A refactoring of the visualization tools in VISCLAW, along with support for additional backends, particularly for three-dimensional results (e.g. Mayavi²⁰, VisIt²¹, ParaView²², or yt²³).

625 Acknowledgements

We wish to thank the many people who have made contributions to the CLAWPACK software over the years, including users who have submitted bug reports (or even better, bug fixes!) or have suggested improvements to the software.

629 **References**

- [1] M. ADAMS, P. COLELLA, J. N. JOHNSON, N. D. KEEN, T. J. LIGOCKI, D. F. MARTIN, P. W.
 MCCORQUODALE, D. MODIANO, P. O. SCHWARTZ, T. D. STERNBERG, AND B. VAN STRAALEN,
 Chombo Software Package for AMR Applications Design Document, Tech. Report LBNL-6616E,
 Lawrence Berkeley National Laboratory.
- [2] K. ALLSTADT, Extracting source characteristics and dynamics of the August 2010 Mount Meager
 landslide from broadband seismograms, J. Geophys. Res., 118 (2013), pp. 1472–1490, doi:10.1002/
 jgrf.20110.
- [3] R. W. Anderson, W. J. Arrighi, N. S. Elliott, B. T. N. Gunney, and R. Hornung, SAMRAI, tech. report.
- [4] S. BALAY, J. BROWN, K. BUSCHELMAN, V. EIJKHOUT, W. D. GROPP, D. KAUSHIK, M. G.
 KNEPLEY, L. C. MCINNES, B. F. SMITH, AND H. ZHANG, *PETSc Users Manual*, Tech. Report
 ANL-95/11 Revision 3.1, Argonne National Laboratory, 2010, http://www.mcs.anl.gov/petsc.
- [5] D. BALE, R. J. LEVEQUE, S. MITRAN, AND J. A. ROSSMANITH, A wave-propagation method for conservation laws and balance laws with spatially varying flux functions, SIAM J. Sci. Comput., 24 (2002), pp. 955–978, http://www.amath.washington.edu/~rjl/pubs/vcflux/.
 - ²⁰http://docs.enthought.com/mayavi/mayavi/ ²¹https://visit.llnl.gov ²²http://www.paraview.org/ ²³http://yt-project.org/

- [6] M. BERGER AND J. OLIGER, Adaptive mesh refinement for hyperbolic partial differential equations,
 J. Comput. Phys., 53 (1984), pp. 484–512.
- [7] M. J. BERGER AND P. COLELLA, Local adaptive mesh refinement for shock hydrodynamics, J. Comput. Phys., 82 (1989), pp. 64–84.
- [8] M. J. BERGER, D. L. GEORGE, R. J. LEVEQUE, AND K. T. MANDLI, *The GeoClaw software* for depth-averaged flows with adaptive refinement, Adv. Water Res., 34 (2011), pp. 1195–1206, www.clawpack.org/links/papers/awr11.
- [9] M. J. BERGER AND R. J. LEVEQUE, Adaptive mesh refinement using wave-propagation algorithms
 for hyperbolic systems, SIAM J. Numer. Anal., 35 (1998), pp. 2298-2316, http://epubs.siam.
 org/sam-bin/dbq/article/31597.
- [10] M. J. BERGER AND R. J. LEVEQUE, Adaptive Mesh Refinement Using Wave-Propagation Algorithms for Hyperbolic Systems, SIAM Journal on Numerical Analysis, 35 (1998), pp. 2298–2316, doi:10.2307/2587259.
- [11] M. J. BERGER AND I. RIGOUTSOS, An algorithm for point clustering and grid generation, IEEE Trans. Sys. Man & Cyber., 21 (1991), pp. 1278–1286.
- [12] J. BROWN, M. G. KNEPLEY, AND B. F. SMITH, Run-Time Extensibility and Librarization of Simulation Software, Computing in Science & Engineering, 17 (2015), pp. 38-45, doi:10.1109/MCSE.
 2014.95, http://ieeexplore.ieee.org/lpdocs/epic03/wrapper.htm?arnumber=6894481.
- [13] C. BURSTEDDE, D. A. CALHOUN, K. MANDLI, AND A. R. TERREL, ForestClaw: Hybrid forest-of octrees AMR for hyperbolic conservation laws, in Parallel Computing : Accelerating Computational
 Science and Engineering (CSE), M. Bader, A. Bode, H.-J. Bungartz, M. Gerndt, G. R. Joubert,
 and F. Peters, eds., vol. 25 of Advances in Parallel Computing, IOS Press, 2014, pp. 253–262.
- [14] CLAWPACK DEVELOPMENT TEAM, Clawpack software, 2015, http://www.clawpack.org. Version
 5.3.0.
- [15] B. N. DAVIS AND R. J. LEVEQUE, Adjoint methods for guiding adaptive mesh refinement in wave propagation problems. http://arxiv.org/abs/1511.03645, 2015.
- [16] R. DEITERDING, Block-structured Adaptive Mesh Refinement Theory, Implementation and Application, ESAIM: Proceedings, 34 (2011), pp. 97–150, doi:10.1051/proc/201134002, http: //www.esaim-proc.org/10.1051/proc/201134002.
- [17] L. M. FARIA AND A. R. KASIMOV, Qualitative modeling of the dynamics of detonations with losses, Proceedings of the Combustion Institute, 35 (2015).
- D. GEORGE, Adaptive finite volume methods with well-balanced Riemann solvers for modeling floods
 in rugged terrain: Application to the Malpasset dam-break flood (France, 1959), Int. J. Numer.
 Meth. Fluids, (2010), doi:10.1002/fld.2298, http://www3.interscience.wiley.com/journal/
 123309491/abstract.
- [19] D. L. GEORGE, Numerical approximation of the nonlinear shallow water equations with topography
 and dry-beds: A Godunov-Type scheme, master's thesis, University of Washington, 2004.
- [20] D. L. GEORGE, Finite Volume Methods and Adaptive Refinement for Tsunami Propagation and Inundation, PhD thesis, University of Washington, 2006.
- [21] D. L. GEORGE, Augmented Riemann solvers for the shallow water equations over variable topog raphy with steady states and inundation, J. Comput. Phys., 227 (2008), pp. 3089–3113.

- [22] D. L. GEORGE AND R. M. IVERSON, A depth-averaged debris-flow model that includes the effects
 of evolving dilatancy. II. Numerical predictions and experimental tests, Proceedings of the Royal
 Society A: Mathematical, Physical and Engineering Sciences, 470 (2014), pp. 20130820–20130820,
 doi:10.1098/rspa.2013.0820, http://rspa.royalsocietypublishing.org/cgi/doi/10.1098/
 rspa.2013.0820.
- [23] F. I. GONZÁLEZ, R. J. LEVEQUE, AND L. M. ADAMS, *Tsunami Hazard Assessment of the* Ocosta School Site in Westport, WA, tech. report, Washington State Emergency Management Division, Sept. 2013, https://digital.lib.washington.edu/researchworks/handle/1773/24054
 (accessed 2015-04-28).
- F. I. GONZALEZ, R. J. LEVEQUE, L. M. ADAMS, C. GOLDFINGER, G. R. PRIEST,
 AND K. WANG, Probabilistic Tsunami Hazard Assessment (PTHA) for Crescent City, CA,
 Sept. 2014, https://digital.lib.washington.edu/researchworks/handle/1773/25916 (ac cessed 2015-10-11).
- F. I. GONZÁLEZ, R. J. LEVEQUE, J. VARKOVITZKY, P. CHAMBERLAIN, B. HIRAI, AND D. L.
 GEORGE, *GeoClaw results for the NTHMP tsunami benchmark problems*, 2011. http://depts.
 washington.edu/clawpack/links/nthmp-benchmarks/.
- [26] Y. HADJIMICHAEL, D. I. KETCHESON, L. LÓCZI, AND A. NÉMETH, Strong stability preserving explicit linear multistep methods with variable step size. Submitted. Preprint available at http://arxiv.org/abs/1504.04107., http://arxiv.org/abs/1504.04107.
- ⁷⁰⁵ [27] J. D. HUNTER, *Matplotlib: A 2d graphics environment*, Computing In Science & Engineering, 9 ⁷⁰⁶ (2007), pp. 90–95.
- R. M. IVERSON AND D. L. GEORGE, A depth-averaged debris-flow model that includes the effects of evolving dilatancy. I. Physical basis, Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences, 470 (2014), pp. 20130819–20130819, doi:10.1098/rspa.2013.0819.
- [29] R. M. IVERSON, D. L. GEORGE, K. ALLSTADT, M. E. REID, B. D. COLLINS, J. W. VALLANCE,
 S. P. SCHILLING, J. W. GODT, C. M. CANNON, C. S. MAGIRL, R. L. BAUM, J. A. COE, W. H.
 SCHULZ, AND J. B. BOWER, Landslide mobility and hazards: implications of the 2014 Oso disaster,
 Earth and Planetary Science Letters, 412 (2015), pp. 197–208, doi:10.1016/j.epsl.2014.12.020.
- [30] E. JONES, T. OLIPHANT, P. PETERSON, ET AL., SciPy: Open source scientific tools for Python,
 2001-, http://www.scipy.org/. [Online; accessed 2016-05-13].
- [31] D. I. KETCHESON, K. MANDLI, A. J. AHMADIA, A. ALGHAMDI, M. Q. DE LUNA, M. PARSANI,
 M. G. KNEPLEY, AND M. EMMETT, *Pyclaw: Accessible, extensible, scalable tools for wave propagation problems*, SIAM Journal on Scientific Computing, 34 (2012), pp. C210–C231.
- [32] D. I. KETCHESON, M. PARSANI, AND R. J. LEVEQUE, High-order Wave Propagation Algorithms for Hyperbolic Systems, SIAM Journal on Scientific Computing, 35 (2013), pp. A351–A377, doi:10.
 1137/110830320, arXiv:1111.3499.
- [33] D. I. KETCHESON AND M. QUEZADA DE LUNA, Diffractons: 2D solitary waves in layered periodic
 media, Multiscale Modeling & Simulation, 13 (2015), pp. 440–458.
- [34] J. KIM, Finite volume methods for Tsunamis genereated by submarine landslides, PhD thesis,
 University of Washington, 2014. http://hdl.handle.net/1773/25374.
- [35] J. O. LANGSETH, Wave Propagation Schemes, Operator Splittings, and Front Tracking for Hyperbolic Conservation Laws, PhD thesis, Department of Informatics, University of Oslo, 1996.

- [36] J. O. LANGSETH AND R. J. LEVEQUE, A wave-propagation method for three-dimensional hyperbolic conservation laws, J. Comput. Phys., 165 (2000), pp. 126-166, http://www.amath.
 washington.edu/~rjl/pubs/wp3d/.
- [37] R. J. LEVEQUE, Clawpack v1.0 announcement. http://www.netlib.org/na-digest-html/94/
 v94n44.html#5, 1994.
- [38] R. J. LEVEQUE, Wave propagation algorithms for multi-dimensional hyperbolic systems, J. Comput. Phys., 131 (1997), pp. 327-353, http://www.amath.washington.edu/~rjl/pubs/wpalg/.
- [39] R. J. LEVEQUE, Finite Volume Methods for Hyperbolic Problems, Cambridge University Press,
 2002, http://amath.washington.edu/~claw/book.html.
- [40] R. J. LEVEQUE, A well-balanced path-integral f-wave method for hyperbolic problems with source terms, J. Sci. Comput., 48 (2010), pp. 209–226, doi:10.1007/s10915-010-9411-0.
- [41] R. J. LEVEQUE, D. L. GEORGE, AND M. J. BERGER, *Tsunami modeling with adaptively refined finite volume methods*, Acta Numerica, (2011), pp. 211–289.
- [42] K. T. MANDLI, Finite Volume Methods for the Multilayer Shallow Water Equations with Applications to Storm Surges, PhD thesis, University of Washington, 2011.
- [43] K. T. MANDLI, A Numerical Method for the Two Layer Shallow Water Equations with Dry States,
 Ocean Modelling, 72 (2013), pp. 80–91, doi:10.1016/j.ocemod.2013.08.001.
- [44] K. T. MANDLI AND C. N. DAWSON, Adaptive Mesh Refinement for Storm Surge, Ocean
 Modelling, 75 (2014), pp. 36-50, http://www.sciencedirect.com/science/article/pii/
 S1463500314000031.
- ⁷⁴⁸ [45] MATLAB, version 8.5.0 (R2015a), The MathWorks Inc., Natick, Massachusetts, 2015a.
- ⁷⁴⁹ [46] OPENFOAM FOUNDATION, *OpenFOAM*, http://openfoam.org/.
- ⁷⁵⁰ [47] F. PÉREZ AND B. E. GRANGER, *Ipython: A system for interactive scientific computing*, Comput-⁷⁵¹ ing in Science and Engineering, 9 (2007).
- [48] P. PETERSON, F2PY: a tool for connecting Fortran and Python programs, International Jour nal of Computational Science and Engineering, 4 (2009), http://dl.acm.org/citation.cfm?id=
 1647766.
- [49] H. A. PIWOWAR, R. S. DAY, AND D. B. FRIDSMA, Sharing detailed research data is associated
 with increased citation rate, PloS One, 2 (2007), p. e308.
- ⁷⁵⁷ [50] S. POPINET, The Gerris Flow Solver, (2001).
- [51] D. SAN ROMAN ALERIGI, Exploring Heterogeneous Time-Varying Materials for Photonic Applications, Towards Solutions for the Manipulation and Confinement of Light, PhD thesis, King
 Abdullah University of Science and Technology, 2015.
- [52] C. D. TEAM, Clawpack version 5.3.1, Nov. 2015, doi:10.5281/zenodo.50982, http://dx.doi.
 org/10.5281/zenodo.50982.
- [53] M. J. TURK, Scaling a code in the human dimension, ACM, July 2013, doi:10.1145/2484762.
 2484782.
- P. VANDEWALLE, Code sharing is associated with research impact in image processing, Comput.
 Sci. Eng., 14 (2012), pp. 42–47.